

What is claimed is;

1. A surface position detection device for detecting a surface position of a detection target surface, comprising;

a projection system that projects a light flux from a diagonal direction onto the detection target surface;

a light-receiving system that receives a light flux having been reflected at the detection target surface; and

a means for light flux deflection provided, at least, either in an optical path of said projection system or in an optical path of said light-receiving system and having an even number of reflection surfaces to allow an incident light flux to exit at an angle that is not parallel to the incident light flux, wherein:

the surface position of the detection target surface is detected based upon an output from said light receiving system.

2. A surface position detection device for detecting a surface position of a detection target surface, comprising;

a projection system that projects a light flux from a diagonal direction onto the detection target surface;

a light-receiving system that receives a light flux having been reflected at the detection target surface; and

a means for light flux deflection provided, at least, either in an optical path of said projection system or in an optical path of said light-receiving system and having an even number of reflection surfaces to allow an incident light flux to exit at an angle that is not parallel to the incident light flux, which includes a prism having a pair of reflection surfaces that are not parallel to each other, wherein:

the surface position of the detection target surface is detected based upon an output from said light-receiving system.

姓名	性别	年龄	籍贯	职业	住址	电话	备注
王德胜	男	45	山东	教师	北京路123号	12345678	
李小红	女	32	江苏	医生	文化路456号	87654321	
张小明	男	28	浙江	工程师	建设路789号	98765432	
赵大伟	男	50	河南	工人	工业路101号	11223344	
陈丽娟	女	38	湖北	会计	商业路202号	22334455	
周国强	男	42	四川	农民	农村路303号	33445566	
吴小芳	女	25	广东	学生	学校路404号	44556677	
孙建刚	男	35	安徽	干部	政府路505号	55667788	
郑美玲	女	30	湖南	护士	医院路606号	66778899	
冯志远	男	48	江西	教授	大学路707号	77889900	
马海燕	女	22	广西	记者	报社路808号	88990011	
徐文涛	男	33	福建	商人	市场路909号	99001122	
黄晓燕	女	27	山西	歌手	音乐路010号	00112233	
郭伟明	男	37	陕西	律师	法院路1011号	11223344	
梁小华	女	23	甘肃	画家	艺术路2012号	22334455	
周俊杰	男	31	宁夏	程序员	科技路3013号	33445566	
吴静怡	女	26	青海	舞蹈家	剧院路4014号	44556677	
孙浩然	男	34	内蒙古	作家	书店路5015号	55667788	
郑雅婷	女	29	海南	模特	时尚路6016号	66778899	
冯天宇	男	41	重庆	科学家	实验室路7017号	77889900	
马晓琳	女	24	贵州	空姐	机场路8018号	88990011	
徐文博	男	36	云南	厨师	餐厅路9019号	99001122	
黄小梅	女	21	四川	歌手	音乐路0120号	00112233	
郭志强	男	39	湖北	工程师	建设路1021号	11223344	
梁丽娟	女	28	湖南	护士	医院路2022号	22334455	
周国强	男	43	江西	教授	大学路3023号	33445566	
吴小芳	女	25	广西	学生	学校路4024号	44556677	
孙建刚	男	35	安徽	干部	政府路5025号	55667788	
郑美玲	女	30	福建	商人	市场路6026号	66778899	
冯志远	男	48	山西	工人	工业路7027号	77889900	
马海燕	女	22	陕西	记者	报社路8028号	88990011	
徐文涛	男	33	甘肃	画家	艺术路9029号	99001122	
黄晓燕	女	27	宁夏	舞蹈家	剧院路0130号	00112233	
郭伟明	男	37	青海	程序员	科技路1031号	11223344	
梁小华	女	23	内蒙古	歌手	音乐路2032号	22334455	
周俊杰	男	31	海南	模特	时尚路3033号	33445566	
吴静怡	女	26	重庆	空姐	机场路4034号	44556677	
孙浩然	男	34	贵州	厨师	餐厅路5035号	55667788	
郑雅婷	女	29	云南	歌手	音乐路6036号	66778899	
冯天宇	男	41	四川	教授	大学路7037号	77889900	
马晓琳	女	24	湖北	护士	医院路8038号	88990011	
徐文博	男	36	江西	工程师	建设路9039号	99001122	
黄小梅	女	21	湖南	学生	学校路0140号	00112233	
郭志强	男	39	广西	干部	政府路1041号	11223344	
梁丽娟	女	28	安徽	商人	市场路2042号	22334455	
周国强	男	43	福建	工人	工业路3043号	33445566	
吴小芳	女	25	山西	记者	报社路4044号	44556677	
孙建刚	男	35	甘肃	画家	艺术路5045号	55667788	
郑美玲	女	30	宁夏	舞蹈家	剧院路6046号	66778899	
冯志远	男	48	青海	程序员	科技路7047号	77889900	
马海燕	女	22	内蒙古	歌手	音乐路8048号	88990011	
徐文涛	男	33	海南	模特	时尚路9049号	99001122	
黄晓燕	女	27	重庆	空姐			

FNKN01001/US

43/102

3. A surface position detection device according to claim 2,  
wherein:

said prism is constituted of an optical material having a coefficient of thermal expansion equal to or lower than 1 ppm/K, which does not expand readily in heat.

4. A surface position detection device for detecting a surface position of a detection target surface, comprising;

a projection system that projects a light flux from a diagonal direction onto the detection target surface;

a light-receiving system that receives a light flux having been reflected at the detection target surface; and

a means for light flux deflection provided, at least, either in an optical path of said projection system or in an optical path of said light-receiving system and having an even number of reflection surfaces to allow an incident light flux to exit at an angle that is not parallel to the incident light flux, which includes a prism having a pair of reflection surfaces that are not parallel to each other and constituted of a low-dispersion optical material with an Abbe number of 65 or higher, wherein:

the surface position of the detection target surface is detected based upon an output from said light-receiving system.

5. A surface position detection device according to claim 4,  
wherein:

said prism is constituted of an optical material having a coefficient of thermal expansion equal to or lower than 1 ppm/K, which does not expand readily in heat.

FNKN01001/US

44/102

6. A surface position detection device for detecting a surface position of a detection target surface, comprising;

a projection system that projects a light flux from a diagonal direction onto the detection target surface;

a light-receiving system that receives a light flux having been reflected at the detection target surface; and

a means for light flux deflection provided, at least, either in an optical path of said projection system or in an optical path of said light-receiving system and having an even number of reflection surfaces to allow an incident light flux to exit at an angle that is not parallel to the incident light flux, which includes a prism having a pair of reflection surfaces that are not parallel to each other, wherein:

said prism includes a first transmission surface through which the incident light flux is transmitted, a first reflection surface at which the light flux having been transmitted through said first transmission surface and propagated through the inside of said prism is reflected, a second reflection surface at which the light flux having been reflected at said first reflection surface and propagated through the inside of said prim is reflected along an optical path intersecting the optical path of the light flux having been transmitted through said first transmission surface and a second transmission surface through which the light flux having been reflected at said second reflection surface and propagated through the inside of said prism is transmitted; and

the surface position of the detection target surface is detected based upon an output from said light-receiving system.

7. A surface position detection device according to claim 6, wherein:

FOUO 20010411

FNKN01001/US

45/102

said prism is constituted of an optical material having a coefficient of thermal expansion equal to or lower than 1 ppm/K, which does not expand readily in heat.

8. A surface position detection device for detecting a surface position of a detection target surface, comprising;

a projection system that projects a light flux from a diagonal direction onto the detection target surface;

a light-receiving system that receives a light flux having been reflected at the detection target surface; and

a means for light flux deflection provided, at least, either in an optical path of said projection system or in an optical path of said light-receiving system and having an even number of reflection surfaces to allow an incident light flux to exit at an angle that is not parallel to the incident light flux, which includes a prism having a pair of reflection surfaces that are not parallel to each other, wherein:

said prism includes a first transmission surface through which the incident light flux is transmitted, a first reflection surface at which the light flux having been transmitted through said first transmission surface and propagated through the inside of said prism is reflected, a second reflection surface at which the light flux having been reflected at said first reflection surface and propagated through the inside of said prism is reflected along an optical path intersecting the optical path of the light flux having been transmitted through said first transmission surface and a second transmission surface through which the light flux having been reflected at said second reflection surface and propagated through the inside of said prism is transmitted and is constituted of a low-dispersion optical material with an Abbe number of 65 or higher; and

the surface position of the detection target surface is detected based upon an output from said light-receiving system.

9. A surface position detection device according to claim 8, wherein:

said prism is constituted of an optical material having a coefficient of thermal expansion equal to or lower than 1 ppm/K, which does not expand readily in heat.

10. A surface position detection device for detecting a surface position of a detection target surface, comprising;

a projection system that projects a light flux from a diagonal direction onto the detection target surface;

a light-receiving system that receives a light flux having been reflected at the detection target surface; and

a means for light flux deflection provided, at least, either in an optical path of said projection system or in an optical path of said light-receiving system and having an even number of reflection surfaces to allow an incident light flux to exit at an angle that is not parallel to the incident light flux, which includes a prism having a pair of reflection surfaces that are not parallel to each other, wherein:

said prism includes a first transmission surface through which the incident light flux is transmitted, a first reflection surface at which the light flux having been transmitted through said first transmission surface and propagated through the inside of said prism is reflected, a second reflection surface at which the light flux having been reflected at said first reflection surface and propagated through the inside of said prism is reflected along an optical path intersecting the optical path of the light flux having been transmitted through said first transmission surface and a second transmission surface through

00032227 0412001

FNKN01001/US

47/102

which the light flux having been reflected at said second reflection surface and propagated through the inside of said prism is transmitted, with the angle formed by said first reflection surface and said second reflection surface set within a range of  $40^\circ$  or more and less than  $45^\circ$ ; and

the surface position of the detection/target surface is detected based upon an output from said light-receiving system.

11. A surface position detection device according to claim 10,  
wherein:

said prism is constituted of an optical material having a coefficient of thermal expansion equal to or lower than 1 ppm/K, which does not expand readily in heat.

12. A surface position detection device for detecting a surface position of a detection target surface, comprising;

a projection system that projects a light flux from a diagonal direction onto the detection target surface;

a light-receiving system that receives a light flux having been reflected at the detection target surface; and

a means for light flux deflection provided, at least, either in an optical path of said projection system or in an optical path of said light-receiving system and having an even number of reflection surfaces to allow an incident light flux to exit at an angle that is not parallel to the incident light flux, which includes a prism having a pair of reflection surfaces that are not parallel to each other, wherein:

said prism includes a first transmission surface through which the incident light flux is transmitted, a first reflection surface at which the light flux having been transmitted through said first transmission surface and propagated through the inside of said prism is reflected, a

second reflection surface at which the light flux having been reflected at said first reflection surface and propagated through the inside of said prism is reflected along an optical path intersecting the optical path of the light flux having been transmitted through said first transmission surface and a second transmission surface through which the light flux having been reflected at said second reflection surface and propagated through the inside of said prism is transmitted, with the angle formed by said first reflection surface and said second reflection surface set within a range of  $40^\circ$  or more and less than  $45^\circ$  and is constituted of a low-dispersion optical material with an Abbe number of 65 or higher ; and

the surface position of the detection target surface is detected based upon an output from said light-receiving system.

13. A surface position detection device according to claim 12,  
wherein:

said prism is constituted of an optical material having a coefficient of thermal expansion equal to or lower than 1 ppm/K, which does not expand readily in heat.

14. A surface position detection device for detecting a surface position of a detection target surface, comprising;

— a projection system that projects a light flux from a diagonal direction onto the detection target surface and includes a projection optical system provided to form a primary image of a specific pattern onto the detection target surface;

a light-receiving system that receives a light flux having been reflected at the detection target surface and includes a condenser optical system provided to form a secondary image of the specific pattern by condensing the light flux having been reflected at the

FNKN01001/US

49/102

detection target surface and a detection unit provided to detect the secondary image of the specific pattern formed via said condenser optical system; and

a means for light flux deflection provided, at least, either in an optical path of said projection system or in an optical path of said light-receiving system and having an even number of reflection surfaces to allow an incident light flux to exit at an angle that is not parallel to the incident light flux, wherein:

the surface position of the detection target surface is detected based upon an output from said detection unit.

15. A surface position detection device for detecting a surface position of a detection target surface, comprising;

a projection system that projects a light flux from a diagonal direction onto the detection target surface and includes a projection optical system provided to form a primary image of a specific pattern onto the detection target surface;

a light-receiving system that receives a light flux having been reflected at the detection target surface and includes a condenser optical system provided to form a secondary image of the specific pattern by condensing the light flux having been reflected at the detection target surface and a detection unit provided to detect the secondary image of the specific pattern formed via said condenser optical system; and

a means for light flux deflection provided, at least, either in an optical path of said projection system or in an optical path of said light-receiving system and having an even number of reflection surfaces to allow an incident light flux to exit at an angle that is not parallel to the incident light flux, which includes a prism having a pair of reflection surfaces that are not parallel to each other, wherein:

0033337-041201



FNKN01001/US

50/102

the surface position of the detection target surface is detected based upon an output from said detection unit.

16. A surface position detection device according to claim 15,  
wherein:

said prism is constituted of an optical material having a coefficient of thermal expansion equal to or lower than 1 ppm/K, which does not expand readily in heat.

17. A surface position detection device for detecting a surface position of a detection target surface, comprising;

a projection system that projects a light flux from a diagonal direction onto the detection target surface and includes a projection optical system provided to form a primary image of a specific pattern onto the detection target surface;

a light-receiving system that receives a light flux having been reflected at the detection target surface and includes a condenser optical system provided to form a secondary image of the specific pattern by condensing the light flux having been reflected at the detection target surface and a detection unit provided to detect the secondary image of the specific pattern formed via said condenser optical system; and

a means for light flux deflection provided, at least, either in an optical path of said projection system or in an optical path of said light-receiving system and having an even number of reflection surfaces to allow an incident light flux to exit at an angle that is not parallel to the incident light flux, which includes a prism having a pair of reflection surfaces that are not parallel to each other and constituted of a low-dispersion optical material with an Abbe number of 65 or higher, wherein:

FNKN01001/US

51/102

the surface position of the detection target surface is detected based upon an output from said detection unit.

18. A surface position detection device according to claim 17,  
wherein:

said prism is constituted of an optical material having a coefficient of thermal expansion equal to or lower than 1 ppm/K, which does not expand readily in heat.

19. A surface position detection device for detecting a surface position of a detection target surface, comprising;

a projection system that projects a light flux from a diagonal direction onto the detection target surface and includes a projection optical system provided to form a primary image of a specific pattern onto the detection target surface;

a light-receiving system that receives a light flux having been reflected at the detection target surface and includes a condenser optical system provided to form a secondary image of the specific pattern by condensing the light flux having been reflected at the detection target surface and a detection unit provided to detect the secondary image of the specific pattern formed via said condenser optical system; and

— a means for light flux deflection provided, at least, either in an optical path of said projection system or in an optical path of said light-receiving system and having an even number of reflection surfaces to allow an incident light flux to exit at an angle that is not parallel to the incident light flux, which includes a prism having a pair of reflection surfaces that are not parallel to each other, wherein:

said prism includes a first transmission surface through which the incident light flux is transmitted, a first reflection surface at which

FNKN01001/US

52/102

the light flux having been transmitted through said first transmission surface and propagated through the inside of said prism is reflected, a second reflection surface at which the light flux having been reflected at said first reflection surface and propagated through the inside of said prism is reflected along an optical path intersecting the optical path of the light flux having been transmitted through said first transmission surface and a second transmission surface through which the light flux having been reflected at said second reflection surface and propagated through the inside of said prism is transmitted; and

the surface position of the detection target surface is detected based upon an output from said detection unit.

20. A surface position detection device according to claim 19,  
wherein:

said prism is constituted of an optical material having a coefficient of thermal expansion equal to or lower than 1 ppm/K, which does not expand readily in heat.

21. A surface position detection device for detecting a surface position of a detection target surface, comprising;

a projection system that projects a light flux from a diagonal direction onto the detection target surface and includes a projection optical system provided to form a primary image of a specific pattern onto the detection target surface;

a light-receiving system that receives a light flux having been reflected at the detection target surface and includes a condenser optical system provided to form a secondary image of the specific pattern by condensing the light flux having been reflected at the detection target surface and a detection unit provided to detect the

FNKN01001/US

53/102

secondary image of the specific pattern formed via said condenser optical system; and

a means for light flux deflection provided, at least, either in an optical path of said projection system or in an optical path of said light-receiving system and having an even number of reflection surfaces to allow an incident light flux to exit at an angle that is not parallel to the incident light flux, which includes a prism having a pair of reflection surfaces that are not parallel to each other, wherein:

said prism includes a first transmission surface through which the incident light flux is transmitted, a first reflection surface at which the light flux having been transmitted through said first transmission surface and propagated through the inside of said prism is reflected, a second reflection surface at which the light flux having been reflected at said first reflection surface and propagated through the inside of said prism is reflected along an optical path intersecting the optical path of the light flux having been transmitted through said first transmission surface and a second transmission surface through which the light flux having been reflected at said second reflection surface and propagated through the inside of said prism is transmitted and is constituted of a low-dispersion optical material with an Abbe number of 65 or higher; and

the surface position of the detection target surface is detected based upon an output from said detection unit.

22. A surface position detection device according to claim 21, wherein:

said prism is constituted of an optical material having a coefficient of thermal expansion equal to or lower than 1 ppm/K, which does not expand readily in heat.

FNKN01001/US

54/102

23. A surface position detection device for detecting a surface position of a detection target surface, comprising;

a projection system that projects a light flux from a diagonal direction onto the detection target surface and includes a projection optical system provided to form a primary image of a specific pattern onto the detection target surface;

a light-receiving system that receives a light flux having been reflected at the detection target surface and includes a condenser optical system provided to form a secondary image of the specific pattern by condensing the light flux having been reflected at the detection target surface and a detection unit provided to detect the secondary image of the specific pattern formed via said condenser optical system; and

a means for light flux deflection provided, at least, either in an optical path of said projection system or in an optical path of said light-receiving system and having an even number of reflection surfaces to allow an incident light flux to exit at an angle that is not parallel to the incident light flux, which includes a prism having a pair of reflection surfaces that are not parallel to each other, wherein:

said prism includes a first transmission surface through which the incident light flux is transmitted, a first reflection surface at which the light flux having been transmitted through said first transmission surface and propagated through the inside of said prism is reflected, a second reflection surface at which the light flux having been reflected at said first reflection surface and propagated through the inside of said prim is reflected along an optical path intersecting the optical path of the light flux having been transmitted through said first transmission surface and a second transmission surface through which the light flux having been reflected at said second reflection surface and propagated through the inside of said prism is

FOUO 46666666

FNKNO1001/US

55/102

transmitted, with the angle formed by said first reflection surface and said second reflection surface set within a range of 40° or more and less than 45°; and

the surface position of the detection target surface is detected based upon an output from said detection unit.

24. A surface position detection device according to claim 23,  
wherein:

wherein:  
said prism is constituted of an optical material having a coefficient of thermal expansion equal to or lower than 1 ppm/K, which does not expand readily in heat.

25. A surface position detection device for detecting a surface position of a detection target surface, comprising;

a projection system that projects a light flux from a diagonal direction onto the detection target surface and includes a projection optical system provided to form a primary image of a specific pattern onto the detection target surface;

a light-receiving system that receives a light flux having been reflected at the detection target surface and includes a condenser optical system provided to form a secondary image of the specific pattern by condensing the light flux having been reflected at the detection target surface and a detection unit provided to detect the secondary image of the specific pattern formed via said condenser optical system; and

a means for light flux deflection provided, at least, either in an optical path of said projection system or in an optical path of said light-receiving system and having an even number of reflection surfaces to allow an incident light flux to exit at an angle that is not



FNKN01001/US

57/102

a light-receiving system that receives a light flux having been reflected at the detection target surface; and

a means for light flux deflection provided, at least, either in an optical path of said projection system or in an optical path of said light-receiving system and having an even number of reflection surfaces to allow an incident light flux to exit at an angle that is not parallel to the incident light flux, which includes a pair of reflection mirrors that are not parallel to each other and holding members each provided to interfit with and hold one of said pair of reflecting mirrors, wherein:

the surface position of the detection/target surface is detected based upon an output from said light-receiving system.

28. A surface position detection device according to claim 27,  
wherein:

said holding members are constituted of an optical material having a coefficient of thermal expansion equal to or lower than 1 ppm/K, which does not expand readily in heat.

29. A surface position detection device for detecting a surface position of a detection target surface, comprising;

a projection system that projects a light flux from a diagonal direction onto the detection target surface and includes a projection optical system provided to form a primary image of a specific pattern onto the detection target surface;

a light-receiving system that receives a light flux having been reflected at the detection target surface and includes a condenser optical system provided to form a secondary image of the specific pattern by condensing the light flux having been reflected at the detection target surface and a detection unit provided to detect the





FNKN01001/US

59/102

a light-receiving system that receives a light flux having been reflected at the detection target surface; and

a means for light flux deflection provided, at least, either in an optical path of said projection system or in an optical path of said light-receiving system and having an even number of reflection surfaces to allow an incident light flux to exit at an angle that is not parallel to the incident light flux; to detect the surface position of the detection target surface is based upon an output from said light-receiving system; and

a means for alignment that aligns the pattern surface at the mask or the exposure target surface of the photosensitive substrate relative to said projection optical system based upon results of a detection performed by said surface position detection device.

32. An exposure apparatus that performs projection exposure of a pattern formed at a mask onto a photosensitive substrate via a projection optical system, comprising;

a surface position detection device that detects a surface position of the pattern surface at the mask or an exposure target surface of the photosensitive substrate relative to said projection optical system as a surface position of a detection target surface and includes;

— a projection system that projects a light flux from a diagonal direction onto the detection target surface;

a light-receiving system that receives a light flux having been reflected at the detection target surface; and

a means for light flux deflection provided, at least, either in an optical path of said projection system or in an optical path of said light-receiving system and having an even number of reflection surfaces to allow an incident light flux to exit at an angle that is not

FNKN01001/US

60/102

parallel to the incident light flux, which includes a prism having a pair of reflection surfaces that are not parallel to each other; to detect the surface position of the detection target surface is detected based upon an output from said light-receiving system; and

a means for alignment that aligns the pattern surface at the mask or the exposure target surface of the photosensitive substrate relative to said projection optical system based upon results of a detection performed by said surface position detection device.

33. An exposure apparatus according to claim 32, wherein:

said prism is constituted of an optical material having a coefficient of thermal expansion equal to or lower than 1 ppm/K, which does not expand readily in heat.

34. An exposure apparatus that performs projection exposure of a pattern formed at a mask onto a photosensitive substrate via a projection optical system, comprising;

a surface position detection device that detects a surface position of the pattern surface at the mask or an exposure target surface of the photosensitive substrate relative to said projection optical system as a surface position of a detection target surface and includes;

a projection system that projects a light flux from a diagonal direction onto the detection target surface;

a light-receiving system that receives a light flux having been reflected at the detection target surface; and

a means for light flux deflection provided, at least, either in an optical path of said projection system or in an optical path of said light-receiving system and having an even number of reflection surfaces to allow an incident light flux to exit at an angle that is not

FNKN01001/U

61/102

parallel to the incident light flux, which includes a prism having a pair of reflection surfaces that are not parallel to each other and constituted of a low-dispersion optical material with an Abbe number of 65 or higher; to detect the surface position of the detection target surface based upon an output from said light-receiving system and;

a means for alignment that aligns the pattern surface at the mask or the exposure target surface of the photosensitive substrate relative to said projection optical system based upon results of a detection performed by said surface position detection device.

35. An exposure apparatus according to claim 34, wherein:

35. said prism is constituted of an optical material having a coefficient of thermal expansion equal to or lower than 1 ppm/K, which does not expand readily in heat.

36. An exposure apparatus that performs projection exposure of a pattern formed at a mask onto a photosensitive substrate via a projection optical system, comprising;

a surface position detection device that detects a surface position of the pattern surface at the mask or an exposure target surface of the photosensitive substrate relative to said projection optical system as a surface position of a detection target surface and includes;

a projection system that projects a light flux from a diagonal direction onto the detection target surface;

a light-receiving system that receives a light flux having been reflected at the detection target surface; and

a means for light flux deflection provided, at least, either in an optical path of said projection system or in an optical path of said light-receiving system and having an even number of reflection



a surface position detection device that detects a surface position of the pattern surface at the mask or an exposure target surface of the photosensitive substrate relative to said projection optical system as a surface position of a detection target surface and includes;

a projection system that projects a light flux from a diagonal direction onto the detection target surface;

a light-receiving system that receives a light flux having been reflected at the detection target surface; and

a means for light flux deflection provided, at least, either in an optical path of said projection system or in an optical path of said light-receiving system and having an even number of reflection surfaces to allow an incident light flux to exit at an angle that is not parallel to the incident light flux, which includes a prism having a pair of reflection surfaces that are not parallel to each other, with said prism having a first transmission surface through which the incident light flux is transmitted, a first reflection surface at which the light flux having been transmitted through said first transmission surface and propagated through the inside of said prism is reflected, a second reflection surface at which the light flux having been reflected at said first reflection surface and propagated through the inside of said prism is reflected along an optical path intersecting the optical path of the light flux having been transmitted through said first transmission surface and a second transmission surface through which the light flux having been reflected at said second reflection surface and propagated through the inside of said prism is transmitted and constituted of a low-dispersion optical material with an Abbe number of 65 or higher; to detect the surface position of the detection target surface is detected based upon an output from said light-receiving system and;

FOOTNOTES 04-1201

a means for alignment that aligns the pattern surface at the mask or the exposure target surface of the photosensitive substrate relative to said projection optical system based upon results of a detection performed by said surface position detection device.

39. An exposure apparatus according to claim 38, wherein:

said prism is constituted of an optical material having a coefficient of thermal expansion equal to or lower than 1 ppm/K, which does not expand readily in heat.

40. An exposure apparatus that performs projection exposure of a pattern formed at a mask onto a photosensitive substrate via a projection optical system, comprising;

a surface position detection device that detects a surface position of the pattern surface at the mask or an exposure target surface of the photosensitive substrate relative to said projection optical system as a surface position of a detection target surface and includes;

a projection system that projects a light flux from a diagonal direction onto the detection target surface;

a light-receiving system that receives a light flux having been reflected at the detection target surface; and

a means for light flux deflection provided, at least, either in an optical path of said projection system or in an optical path of said light-receiving system and having an even number of reflection surfaces to allow an incident light flux to exit at an angle that is not parallel to the incident light flux, which includes a prism having a pair of reflection surfaces that are not parallel to each other, with said prism having a first transmission surface through which the incident light flux is transmitted, a first reflection surface at which the light

00833037 041204

[illegible]

surface of the  
thermal system  
face position

41. An exposure apparatus according to claim 40, wherein:

41. An exposure apparatus comprising:  
said prism is constituted of an optical material having a coefficient of thermal expansion equal to or lower than 1 ppm/K, which does not expand readily in heat.

42. An exposure apparatus that performs projection exposure of a pattern formed at a mask onto a photosensitive substrate via a projection optical system, comprising;

a surface position detection device that detects a surface position of the pattern surface at the mask or an exposure target surface of the photosensitive substrate relative to said projection





a means for alignment that aligns the pattern surface at the mask or the exposure target surface of the photosensitive substrate relative to said projection optical system based upon results of a detection performed by said surface position detection device.

43. An exposure apparatus according to claim 42, wherein:  
said prism is constituted of an optical material having a  
coefficient of thermal expansion equal to or lower than 1 ppm/K,  
which does not expand readily in heat.

44. An exposure apparatus that performs projection exposure of a pattern formed at a mask onto a photosensitive substrate via a projection optical system, comprising;

a surface position detection device that detects a surface position of the pattern surface at the mask or an exposure target surface of the photosensitive substrate relative to said projection optical system as a surface position of a detection target surface and includes;

includes;  
a projection system that projects a light flux from a diagonal direction onto the detection target surface and includes a projection optical system provided to form a primary image of a specific pattern onto the detection target surface;

onto the detection target surface,  
a light-receiving system that receives a light flux having been reflected at the detection target surface and includes a condenser optical system provided to form a secondary image of the specific pattern by condensing a light flux having been reflected at the detection target surface and a detection unit provided to detect the secondary image of the specific pattern formed via said condenser optical system; and

FNKN01001/US

68/102

a means for light flux deflection provided, at least, either in an optical path of said projection system or in an optical path of said light-receiving system and having an even number of reflection surfaces to allow an incident light flux to exit at an angle that is not parallel to the incident light flux; to detect the surface position of the detection target surface based upon an output from said detection unit and;

a means for alignment that aligns the pattern surface at the mask or the exposure target surface of the photosensitive substrate relative to said projection optical system based upon results of a detection performed by said surface position detection device.

45. An exposure apparatus that performs projection exposure of a pattern formed at a mask onto a photosensitive substrate via a projection optical system, comprising;

a surface position detection device that detects a surface position of the pattern surface at the mask or an exposure target surface of the photosensitive substrate relative to said projection optical system as a surface position of a detection target surface and includes;

a projection system that projects a light flux from a diagonal direction onto the detection target surface and includes a projection optical system provided to form a primary image of a specific pattern onto the detection target surface;

a light-receiving system that receives a light flux having been reflected at the detection target surface and includes a condenser optical system provided to form a secondary image of the specific pattern by condensing a light flux having been reflected at the detection target surface and a detection unit provided to detect the

FNKN01001/US

69/102

secondary image of the specific pattern formed via said condenser optical system; and

a means for light flux deflection provided, at least, either in an optical path of said projection system or in an optical path of said light-receiving system and having an even number of reflection surfaces to allow an incident light flux to exit at an angle that is not parallel to the incident light flux, which includes a prism having a pair of reflection surfaces that are not parallel to each other; to detect the surface position of the detection target surface based upon an output from said detection unit and;

a means for alignment that aligns the pattern surface at the mask or the exposure target surface of the photosensitive substrate relative to said projection optical system based upon results of a detection performed by said surface position detection device.

46. An exposure apparatus according to claim 45, wherein:

said prism is constituted of an optical material having a coefficient of thermal expansion equal to or lower than 1 ppm/K, which does not expand readily in heat.

47. An exposure apparatus that performs projection exposure of a pattern formed at a mask onto a photosensitive substrate via a projection-optical-system, comprising;

a surface position detection device that detects a surface position of the pattern surface at the mask or an exposure target surface of the photosensitive substrate relative to said projection optical system as a surface position of a detection target surface and includes;

a projection system that projects a light flux from a diagonal direction onto the detection target surface and includes a projection

FOOTNOTES 04-1201

optical system provided to form a primary image of a specific pattern onto the detection target surface;

a light-receiving system that receives a light flux having been reflected at the detection target surface and includes a condenser optical system provided to form a secondary image of the specific pattern by condensing a light flux having been reflected at the detection target surface and a detection unit provided to detect the secondary image of the specific pattern formed via said condenser optical system; and

a means for light flux deflection provided, at least, either in an optical path of said projection system or in an optical path of said light-receiving system and having an even number of reflection surfaces to allow an incident light flux to exit at an angle that is not parallel to the incident light flux, which includes a prism having a pair of reflection surfaces that are not parallel to each other and constituted of a low-dispersion optical material with an Abbe number of 65 or higher; to detect the surface position of the detection target surface based upon an output from said detection unit and;

a means for alignment that aligns the pattern surface at the mask or the exposure target surface of the photosensitive substrate relative to said projection optical system based upon results of a detection performed by said surface position detection device.

48. An exposure apparatus according to claim 47, wherein:

48. An exposure apparatus according to claim 47, wherein said prism is constituted of an optical material having a coefficient of thermal expansion equal to or lower than 1 ppm/K, which does not expand readily in heat.

FNKN01001/US

71/102

49. An exposure apparatus that performs projection exposure of a pattern formed at a mask onto a photosensitive substrate via a projection optical system, comprising;

a surface position detection device that detects a surface position of the pattern surface at the mask or an exposure target surface of the photosensitive substrate relative to said projection optical system as a surface position of a detection target surface and includes;

a projection system that projects a light flux from a diagonal direction onto the detection target surface and includes a projection optical system provided to form a primary image of a specific pattern onto the detection target surface;

a light-receiving system that receives a light flux having been reflected at the detection target surface and includes a condenser optical system provided to form a secondary image of the specific pattern by condensing a light flux having been reflected at the detection target surface and a detection unit provided to detect the secondary image of the specific pattern formed via said condenser optical system; and

a means for light flux deflection provided, at least, either in an optical path of said projection system or in an optical path of said light-receiving system and having an even number of reflection surfaces to allow an incident light flux to exit at an angle that is not parallel to the incident light flux, which includes a prism having a pair of reflection surfaces that are not parallel to each other, with said prism having a first transmission surface through which the incident light flux is transmitted, a first reflection surface at which the light flux having been transmitted through said first transmission surface and propagated through the inside of said prism is reflected, a second reflection surface at which the light flux having been reflected at said

FOOTNOTES

FNKN01001/US

72/102

first reflection surface and propagated through the inside of said prism is reflected along an optical path intersecting the optical path of the light flux having been transmitted through said first transmission surface and a second transmission surface through which the light flux having been reflected at said second reflection surface and propagated through the inside of said prism is transmitted; to detect the surface position of the detection target surface based upon an output from said detection unit and;

a means for alignment that aligns the pattern surface at the mask or the exposure target surface of the photosensitive substrate relative to said projection optical system based upon results of a detection performed by said surface position detection device.

50. An exposure apparatus according to claim 49, wherein:

said prism is constituted of an optical material having a coefficient of thermal expansion equal to or lower than 1 ppm/K, which does not expand readily in heat.

51. An exposure apparatus that performs projection exposure of a pattern formed at a mask onto a photosensitive substrate via a projection optical system, comprising;

a surface position detection device that detects a surface position of the pattern surface at the mask or an exposure target surface of the photosensitive substrate relative to said projection optical system as a surface position of a detection target surface and includes;

a projection system that projects a light flux from a diagonal direction onto the detection target surface and includes a projection optical system provided to form a primary image of a specific pattern onto the detection target surface;

FOOTNOTES

FNKN01001/US

73/102

[illegible]

a light-receiving system that receives a light flux having been reflected at the detection target surface and includes a condenser optical system provided to form a secondary image of the specific pattern by condensing a light flux having been reflected at the detection target surface and a detection unit provided to detect the secondary image of the specific pattern formed via said condenser optical system; and

a means for light flux deflection provided, at least, either in an optical path of said projection system or in an optical path of said light-receiving system and having an even number of reflection surfaces to allow an incident light flux to exit at an angle that is not parallel to the incident light flux, which includes a prism having a pair of reflection surfaces that are not parallel to each other, with said prism having a first transmission surface through which the incident light flux is transmitted, a first reflection surface at which the light flux having been transmitted through said first transmission surface and propagated through the inside of said prism is reflected, a second reflection surface at which the light flux having been reflected at said first reflection surface and propagated through the inside of said prism is reflected along an optical path intersecting the optical path of the light flux having been transmitted through said first transmission surface and a second transmission surface through which the light flux having been reflected at said second reflection surface and propagated through the inside of said prism is transmitted and constituted of a low-dispersion optical material with an Abbe number of 65 or higher; to detect the surface position of the detection target surface based upon an output from said detection unit and;

a means for alignment that aligns the pattern surface at the mask or the exposure target surface of the photosensitive substrate



FNKN01001/US

74/102

relative to said projection optical system based upon results of a detection performed by said surface position detection device.

52. An exposure apparatus according to claim 51, wherein:



55. An exposure apparatus that performs projection exposure of a pattern formed at a mask onto a photosensitive substrate via a projection optical system, comprising;

a surface position detection device that detects a surface position of the pattern surface at the mask or an exposure target surface of the photosensitive substrate relative to said projection optical system as a surface position of a detection target surface and includes;

a projection system that projects a light flux from a diagonal direction onto the detection target surface and includes a projection optical system provided to form a primary image of a specific pattern onto the detection target surface;

a light-receiving system that receives a light flux having been reflected at the detection target surface and includes a condenser optical system provided to form a secondary image of the specific pattern by condensing a light flux having been reflected at the detection target surface and a detection unit provided to detect the secondary image of the specific pattern formed via said condenser optical system; and

a means for light flux deflection provided, at least, either in an optical path of said projection system or in an optical path of said light-receiving system and having an even number of reflection surfaces to allow an incident light flux to exit at an angle that is not parallel to the incident light flux, which includes a prism having a pair of reflection surfaces that are not parallel to each other, with said prism having a first transmission surface through which the incident light flux is transmitted, a first reflection surface at which the light flux having been transmitted through said first transmission surface and propagated through the inside of said prism is reflected, a second reflection surface at which the light flux having been reflected at said

0033337-0413074

first reflection surface and propagated through the inside of said prism is reflected along an optical path intersecting the optical path of the light flux having been transmitted through said first transmission surface and a second transmission surface through which the light flux having been reflected at said second reflection surface and propagated through the inside of said prism is transmitted, the angle formed by said first reflection surface and said second reflection surface set within a range of  $40^\circ$  or greater and less than  $45^\circ$  and said prism is constituted of a low-dispersion optical material with an Abbe number of 65 or greater; to detect the surface position of the detection target surface based upon an output from said detection unit and;

a means for alignment that aligns the pattern surface at the mask or the exposure target surface of the photosensitive substrate relative to said projection optical system based upon results of a detection performed by said surface position detection device.

56. An exposure apparatus according to claim 55, wherein:

said prism is constituted of an optical material having a coefficient of thermal expansion equal to or lower than 1 ppm/K, which does not expand readily in heat.

57. An exposure apparatus that performs projection exposure of a pattern formed at a mask onto a photosensitive substrate via a projection optical system, comprising;

a surface position detection device that detects a surface position of the pattern surface at the mask or an exposure target surface of the photosensitive substrate relative to said projection optical system as a surface position of a detection target surface and includes;

FNKN01001/US

FNKN01001/US

79/102

optical system as a surface position of a detection target surface and includes;

a projection system that projects a light flux from a diagonal direction onto the detection target surface and includes a projection optical system provided to form a primary image of a specific pattern onto the detection target surface;

a light-receiving system that receives a light flux having been reflected at the detection target surface and includes a condenser optical system provided to form a secondary image of the specific pattern by condensing the light flux having been reflected at the detection target surface and a detection unit provided to detect the secondary image of the specific pattern formed via said condenser optical system;

a means for light flux deflection provided, at least, either in an optical path of said projection system or in an optical path of said light-receiving system and having an even number of reflection surfaces to allow an incident light flux to exit at an angle that is not parallel to the incident light flux, which includes a pair of reflection mirrors that are not parallel to each other and holding members each provided to interfit with and hold one of said pair of reflecting mirrors; to detect the surface position of the detection target surface based upon an output from said detection unit; and

a means for alignment that aligns the pattern surface at the mask or the exposure target surface of the photosensitive substrate relative to said projection optical system based upon results of a detection performed by said surface position detection device.

60. An exposure apparatus according to claim 59, wherein:

said holding members are constituted of an optical material having a coefficient of thermal expansion equal to or lower than 1 ppm/K, which does not expand readily in heat.

61. An exposure method for implementing projection exposure of a pattern formed at a mask onto a photosensitive substrate via a projection optical system, comprising;

a detection step in which the surface position of a pattern surface of the mask or an exposure target surface of the photosensitive substrate relative to said projection optical system is detected as a surface position of a detection target surface by employing a surface position detection device that detects the surface position of the detection target surface and includes;

a projection system that projects a light flux from a diagonal direction onto the detection target surface;

a light-receiving system that receives a light flux having been reflected at the detection target surface; and

a means for light flux deflection provided, at least, either in an optical path of said projection system or in an optical path of said light-receiving system and having an even number of reflection surfaces to allow an incident light flux to exit at an angle that is not parallel to the incident light flux; to detect the surface position of the detection target surface based upon an output from said light-receiving system; and

an alignment step in which the pattern surface of the mask or the exposure target surface of the photosensitive substrate is aligned relative to said projection optical system based upon results of a detection performed in said detection step.

00000000-00000000

FNKN01001/US

81/102

62. An exposure method for implementing projection exposure of a pattern formed at a mask onto a photosensitive substrate via a projection optical system, comprising;

a detection step in which the surface position of a pattern surface of the mask or an exposure target surface of the photosensitive substrate relative to said projection optical system is detected as a surface position of a detection target surface by employing a surface position detection device that detects the surface position of the detection target surface and includes;

a projection system that projects a light flux from a diagonal direction onto the detection target surface;

a light-receiving system that receives a light flux having been reflected at the detection target surface; and

a means for light flux deflection provided, at least, either in an optical path of said projection system or in an optical path of said light-receiving system and having an even number of reflection surfaces to allow an incident light flux to exit at an angle that is not parallel to the incident light flux, which includes a prism having a pair of reflection surfaces that are not parallel to each other; to detect the surface position of the detection target surface based upon an output from said light-receiving system; and

an alignment step in which the pattern surface of the mask or the exposure target surface of the photosensitive substrate is aligned relative to said projection optical system based upon results of a detection performed in said detection step.

63. An exposure method according to claim 62, wherein:

said prism is constituted of an optical material having a coefficient of thermal expansion equal to or lower than 1 ppm/K, which does not expand readily in heat.

FOUO 2001-04-11





FNKN01001/US

83/102

said prism is constituted of an optical material having a coefficient of thermal expansion equal to or lower than 1 ppm/K, which does not expand readily in heat.

66. An exposure method for implementing projection exposure of a pattern formed at a mask onto a photosensitive substrate via a projection optical system, comprising;

a detection step in which the surface position of a pattern surface of the mask or an exposure target surface of the photosensitive substrate relative to said projection optical system is detected as a surface position of a detection target surface by employing a surface position detection device that detects the surface position of the detection target surface and includes;

a projection system that projects a light flux from a diagonal direction onto the detection target surface;

a light-receiving system that receives a light flux having been reflected at the detection target surface; and

a means for light flux deflection provided, at least, either in an optical path of said projection system or in an optical path of said light-receiving system and having an even number of reflection surfaces to allow an incident light flux to exit at an angle that is not parallel to the incident light flux, which includes a prism having a pair of reflection surfaces that are not parallel to each other, with said prism having a first transmission surface through which the incident light flux is transmitted, a first reflection surface at which the light flux having been transmitted through said first transmission surface and propagated through the inside of said prism is reflected, a second reflection surface at which the light flux having been reflected at said first reflection surface and propagated through the inside of said prism is reflected along an optical path intersecting the optical path of the

FOI b7D - 2000000000

FNKN01001/U

84/102

light flux having been transmitted through said first transmission surface and a second transmission surface through which the light flux having been reflected at said second reflection surface and propagated through the inside of said prism is transmitted; to detect the surface position of the detection target surface based upon an output from said light-receiving system; and

an alignment step in which the pattern surface of the mask or the exposure target surface of the photosensitive substrate is aligned relative to said projection optical system based upon results of a detection performed in said detection step.

67. An exposure method according to claim 66, wherein:

said prism is constituted of an optical material having a coefficient of thermal expansion equal to or lower than 1 ppm/K, which does not expand readily in heat.

68. An exposure method for implementing projection exposure of a pattern formed at a mask onto a photosensitive substrate via a projection optical system, comprising;

a detection step in which the surface position of a pattern surface of the mask or an exposure target surface of the photosensitive substrate relative to said projection optical system is detected as a surface position of a detection target surface by employing a surface position detection device that detects the surface position of the detection target surface and includes;

a projection system that projects a light flux from a diagonal direction onto the detection target surface;

a light-receiving system that receives a light flux having been reflected at the detection target surface; and

FNKN01001/U

85/102

00000000-041001

a means for light flux deflection provided, at least, either in an optical path of said projection system or in an optical path of said light-receiving system and having an even number of reflection surfaces to allow an incident light flux to exit at an angle that is not parallel to the incident light flux, which includes a prism having a pair of reflection surfaces that are not parallel to each other, a first transmission surface through which the incident light flux is transmitted, a first reflection surface at which the light flux having been transmitted through said first transmission surface and propagated through the inside of said prism is reflected, a second reflection surface at which the light flux having been reflected at said first reflection surface and propagated through the inside of said prism is reflected along an optical path intersecting the optical path of the light flux having been transmitted through said first transmission surface and a second transmission surface through which the light flux having been reflected at said second reflection surface and propagated through the inside of said prism is transmitted, and constituted of a low-dispersion optical material with an Abbe number of 65 or higher; to detect the surface position of the detection target surface based upon an output from said light-receiving system; and

an alignment step in which the pattern surface of the mask or the exposure target surface of the photosensitive substrate is aligned relative to said projection optical system based upon results of a detection performed in said detection step.

69. An exposure method according to claim 68, wherein:

said prism is constituted of an optical material having a coefficient of thermal expansion equal to or lower than 1 ppm/K, which does not expand readily in heat.

FNKN01001/U

86/102

70. An exposure method for implementing projection exposure of a pattern formed at a mask onto a photosensitive substrate via a projection optical system, comprising;

a detection step in which the surface position of a pattern surface of the mask or an exposure target surface of the photosensitive substrate relative to said projection optical system is detected as a surface position of a detection target surface by employing a surface position detection device that detects the surface position of the detection target surface and includes;

a projection system that projects a light flux from a diagonal direction onto the detection target surface;

a light-receiving system that receives a light flux having been reflected at the detection target surface; and

a means for light flux deflection provided, at least, either in an optical path of said projection system or in an optical path of said light-receiving system and having an even number of reflection surfaces to allow an incident light flux to exit at an angle that is not parallel to the incident light flux, which includes a prism having a pair of reflection surfaces that are not parallel to each other, a first transmission surface through which the incident light flux is transmitted, a first reflection surface at which the light flux having been transmitted through said first transmission surface and propagated through the inside of said prism is reflected, a second reflection surface at which the light flux having been reflected at said first reflection surface and propagated through the inside of said prism is reflected along an optical path intersecting the optical path of the light flux having been transmitted through said first transmission surface and a second transmission surface through which the light flux having been reflected at said second reflection surface and propagated through the inside of said prism is transmitted, and the

FOOTNOTES

FNKN01001/US

87/102

angle formed by said first reflection surface and said second reflection surface set within a range of  $40^\circ$  or greater and less than  $45^\circ$ ; to detect the surface position of the detection target surface based upon an output from said light-receiving system; and

an alignment step in which the pattern surface of the mask or the exposure target surface of the photosensitive substrate is aligned relative to said projection optical system based upon the results of a detection performed in said detection step.

71. An exposure method according to claim 70, wherein:

said prism is constituted of an optical material having a coefficient of thermal expansion equal to or lower than 1 ppm/K, which does not expand readily in heat.

72. An exposure method for implementing projection exposure of a pattern formed at a mask onto a photosensitive substrate via a projection optical system, comprising:

a detection step in which the surface position of a pattern surface of the mask or an exposure target surface of the photosensitive substrate relative to said projection optical system is detected as a surface position of a detection target surface by employing a surface position detection device that detects the surface position of the detection target surface and includes;

a projection system that projects a light flux from a diagonal direction onto the detection target surface;

a light-receiving system that receives a light flux having been reflected at the detection target surface; and

a means for light flux deflection provided, at least, either in an optical path of said projection system or in an optical path of said light-receiving system and having an even number of reflection

TUEFNU-2E8E860

FNKN01001/US

88/102

surfaces to allow an incident light flux to exit at an angle that is not parallel to the incident light flux, which includes a prism having a pair of reflection surfaces that are not parallel to each other, a first transmission surface through which the incident light flux is transmitted, a first reflection surface at which the light flux having been transmitted through said first transmission surface and propagated through the inside of said prism is reflected, a second reflection surface at which the light flux having been reflected at said first reflection surface and propagated through the inside of said prism is reflected along an optical path intersecting the optical path of the light flux having been transmitted through said first transmission surface and a second transmission surface through which the light flux having been reflected at said second reflection surface and propagated through the inside of said prism is transmitted, and the angle formed by said first reflection surface and said second reflection surface set within a range of  $40^\circ$  or greater and less than  $45^\circ$  and said prism is constituted of a low-dispersion optical material with an Abbe number of 65 or higher; to detect the surface position of the detection target surface based upon an output from said light-receiving system; and

an alignment step in which the pattern surface of the mask or the exposure target surface of the photosensitive substrate is aligned relative to said projection optical system based upon the results of a detection performed in said detection step.

73. An exposure method according to claim 72, wherein:

said prism is constituted of an optical material having a coefficient of thermal expansion equal to or lower than 1 ppm/K, which does not expand readily in heat.

FNKN01001/US

89/102

74. An exposure method for implementing projection exposure of a pattern formed at a mask onto a photosensitive substrate via a projection optical system, comprising;

a detection step in which the surface position of a pattern surface of the mask or an exposure target surface of the photosensitive substrate relative to said projection optical system is detected as a surface position of a detection target surface by employing a surface position detection device that detects the surface position of the detection target surface and includes;

a projection system that projects a light flux from a diagonal direction onto the detection target surface and includes a projection optical system provided to form a primary image of a specific pattern onto the detection target surface;

a light-receiving system that receives a light flux having been reflected at the detection target surface and includes a condenser optical system provided to form a secondary image of the specific pattern by condensing the light flux having been reflected at the detection target surface and a detection unit provided to detect the secondary image of the specific pattern formed via said condenser optical system; and

a means for light flux deflection provided, at least, either in an optical path of said projection system or in an optical path of said light-receiving system and having an even number of reflection surfaces to allow an incident light flux to exit at an angle that is not parallel to the incident light flux; to detect the surface position of the detection target surface based upon an output from said detection unit; and

an alignment step in which the pattern surface of the mask or the exposure target surface of the photosensitive substrate is aligned

00000000-041201



FNKN01001/US

90/102

relative to said projection optical system based upon results of a detection performed in said detection step.

75. An exposure method for implementing projection exposure of a pattern formed at a mask onto a photosensitive substrate via a projection optical system, comprising;

a detection step in which the surface position of a pattern surface of the mask or an exposure target surface of the photosensitive substrate relative to said projection optical system is detected as a surface position of a detection target surface by employing a surface position detection device that detects the surface position of the detection target surface and includes;

a projection system that projects a light flux from a diagonal direction onto the detection target surface and includes a projection optical system provided to form a primary image of a specific pattern onto the detection target surface;

a light-receiving system that receives a light flux having been reflected at the detection target surface and includes a condenser optical system provided to form a secondary image of the specific pattern by condensing the light flux having been reflected at the detection target surface and a detection unit provided to detect the secondary image of the specific pattern formed via said condenser optical system; and

a means for light flux deflection provided, at least, either in an optical path of said projection system or in an optical path of said light-receiving system and having an even number of reflection surfaces to allow an incident light flux to exit at an angle that is not parallel to the incident light flux which includes a prism having a pair of reflection surfaces that are not parallel to each other; to detect the

FNKN01001/US

91/102

surface position of the detection target surface based upon an output from said detection unit; and

an alignment step in which the pattern surface of the mask or the exposure target surface of the photosensitive substrate is aligned relative to said projection optical system based upon results of a detection performed in said detection step.

76. An exposure method according to claim 75, wherein:

said prism is constituted of an optical material having a coefficient of thermal expansion equal to or lower than 1 ppm/K, which does not expand readily in heat.

77. An exposure method for implementing projection exposure of a pattern formed at a mask onto a photosensitive substrate via a projection optical system, comprising;

a detection step in which the surface position of a pattern surface of the mask or an exposure target surface of the photosensitive substrate relative to said projection optical system is detected as a surface position of a detection target surface by employing a surface position detection device that detects the surface position of the detection target surface and includes;

a projection system that projects a light flux from a diagonal direction onto the detection target surface and includes a projection optical system provided to form a primary image of a specific pattern onto the detection target surface;

a light-receiving system that receives a light flux having been reflected at the detection target surface and includes a condenser optical system provided to form a secondary image of the specific pattern by condensing the light flux having been reflected at the detection target surface and a detection unit provided to detect the

FNKN01001/US

92/102

secondary image of the specific pattern formed via said condenser optical system; and

a means for light flux deflection provided, at least, either in an optical path of said projection system or in an optical path of said light-receiving system and having an even number of reflection surfaces to allow an incident light flux to exit at an angle that is not parallel to the incident light flux, which includes a prism having a pair of reflection surfaces that are not parallel to each other and constituted of a low-dispersion optical material with an Abbe number of 65 or higher; to detect the surface position of the detection target surface based upon an output from said detection unit; and

an alignment step in which the pattern surface of the mask or the exposure target surface of the photosensitive substrate is aligned relative to said projection optical system based upon results of a detection performed in said detection step.

78. An exposure method according to claim 77, wherein:

said prism is constituted of an optical material having a coefficient of thermal expansion equal to or lower than 1 ppm/K, which does not expand readily in heat.

79. An exposure method for implementing projection exposure of a pattern formed at a mask onto a photosensitive substrate via a projection optical system, comprising;

a detection step in which the surface position of a pattern surface of the mask or an exposure target surface of the photosensitive substrate relative to said projection optical system is detected as a surface position of a detection target surface by employing a surface position detection device that detects the surface position of the detection target surface and includes;

FNKN01001/US

93/102

FOUO 42000000

a projection system that projects a light flux from a diagonal direction onto the detection target surface and includes a projection optical system provided to form a primary image of a specific pattern onto the detection target surface;

a light-receiving system that receives a light flux having been reflected at the detection target surface and includes a condenser optical system provided to form a secondary image of the specific pattern by condensing the light flux having been reflected at the detection target surface and a detection unit provided to detect the secondary image of the specific pattern formed via said condenser optical system; and

a means for light flux deflection provided, at least, either in an optical path of said projection system or in an optical path of said light-receiving system and having an even number of reflection surfaces to allow an incident light flux to exit at an angle that is not parallel to the incident light flux which includes a prism having a pair of reflection surfaces that are not parallel to each other, a first transmission surface through which the incident light flux is transmitted, a first reflection surface at which the light flux having been transmitted through said first transmission surface and propagated through the inside of said prism is reflected, a second reflection surface at which the light flux having been reflected at said first reflection surface and propagated through the inside of said prism is reflected along an optical path intersecting the optical path of the light flux having been transmitted through said first transmission surface and a second transmission surface through which the light flux having been reflected at said second reflection surface and propagated through the inside of said prism is transmitted; to detect the surface position of the detection target surface based upon an output from said detection unit; and

FNKN01001/US

94/102

an alignment step in which the pattern surface of the mask or the exposure target surface of the photosensitive substrate is aligned relative to said projection optical system based upon results of a detection performed in said detection step.

80. An exposure method according to claim 79, wherein:

said prism is constituted of an optical material having a coefficient of thermal expansion equal to or lower than 1 ppm/K, which does not expand readily in heat.

81. An exposure method for implementing projection exposure of a pattern formed at a mask onto a photosensitive substrate via a projection optical system, comprising;

a detection step in which the surface position of a pattern surface of the mask or an exposure target surface of the photosensitive substrate relative to said projection optical system is detected as a surface position of a detection target surface by employing a surface position detection device that detects the surface position of the detection target surface and includes;

a projection system that projects a light flux from a diagonal direction onto the detection target surface and includes a projection optical system provided to form a primary image of a specific pattern onto the detection target surface;

a light-receiving system that receives a light flux having been reflected at the detection target surface and includes a condenser optical system provided to form a secondary image of the specific pattern by condensing the light flux having been reflected at the detection target surface and a detection unit provided to detect the secondary image of the specific pattern formed via said condenser optical system; and

FNKN01001/US

95/102

a means for light flux deflection provided, at least, either in an optical path of said projection system or in an optical path of said light-receiving system and having an even number of reflection surfaces to allow an incident light flux to exit at an angle that is not parallel to the incident light flux, which includes a prism having a pair of reflection surfaces that are not parallel to each other, a first transmission surface through which the incident light flux is transmitted, a first reflection surface at which the light flux having been transmitted through said first transmission surface and propagated through the inside of said prism is reflected, a second reflection surface at which the light flux having been reflected at said first reflection surface and propagated through the inside of said prism is reflected along an optical path intersecting the optical path of the light flux having been transmitted through said first transmission surface and a second transmission surface through which the light flux having been reflected at said second reflection surface and propagated through the inside of said prism is transmitted, and constituted of a low-dispersion optical material with an Abbe number of 65 or higher; to detect the surface position of the detection target surface based upon an output from said detection unit; and

an alignment step in which the pattern surface of the mask or the exposure target surface of the photosensitive substrate is aligned relative to said projection/optical system based upon results of a detection performed in said detection step.

82. An exposure method according to claim 81, wherein:

said prism is constituted of an optical material having a coefficient of thermal expansion equal to or lower than 1 ppm/K, which does not expand readily in heat.

FNKN01001/US

96/102

83. An exposure method for implementing projection exposure of a pattern formed at a mask onto a photosensitive substrate via a projection optical system, comprising;

a detection step in which the surface position of a pattern surface of the mask or an exposure target surface of the photosensitive substrate relative to said projection optical system is detected as a surface position of a detection target surface by employing a surface position detection device that detects the surface position of the detection target surface and includes;

a projection system that projects a light flux from a diagonal direction onto the detection target surface and includes a projection optical system provided to form a primary image of a specific pattern onto the detection target surface;

a light-receiving system that receives a light flux having been reflected at the detection target surface and includes a condenser optical system provided to form a secondary image of the specific pattern by condensing the light flux having been reflected at the detection target surface and a detection unit provided to detect the secondary image of the specific pattern formed via said condenser optical system; and

a means for light flux deflection provided, at least, either in an optical path of said projection system or in an optical path of said light-receiving system and having an even number of reflection surfaces to allow an incident light flux to exit at an angle that is not parallel to the incident light flux, which includes a prism having a pair of reflection surfaces that are not parallel to each other, a first transmission surface through which the incident light flux is transmitted, a first reflection surface at which the light flux having been transmitted through said first transmission surface and propagated through the inside of said prism is reflected, a second

FNKN01001/US

97/102

reflection surface at which the light flux having been reflected at said first reflection surface and propagated through the inside of said prism is reflected along an optical path intersecting the optical path of the light flux having been transmitted through said first transmission surface and a second transmission surface through which the light flux having been reflected at said second reflection surface and propagated through the inside of said prism is transmitted, and the angle formed by said first reflection surface and said second reflection surface set within a range of  $40^\circ$  or greater and less than  $45^\circ$ ; to detect the surface position of the detection target surface based upon an output from said detection unit; and

an alignment step in which the pattern surface of the mask or the exposure target surface of the photosensitive substrate is aligned relative to said projection optical system based upon results of a detection performed in said detection step.

84. An exposure method according to claim 83, wherein:

said prism is constituted of an optical material having a coefficient of thermal expansion equal to or lower than 1 ppm/K, which does not expand readily in heat.

85. An exposure method for implementing projection exposure of a pattern formed at a mask onto a photosensitive substrate via a projection optical system, comprising;

a detection step in which the surface position of a pattern surface of the mask or an exposure target surface of the photosensitive substrate relative to said projection optical system is detected as a surface position of a detection target surface by employing a surface position detection device that detects the surface position of the detection target surface and includes;

FOOTNO 041201



FNKN01001/US

98/102

a projection system that projects a light flux from a diagonal direction onto the detection target surface and includes a projection optical system provided to form a primary image of a specific pattern onto the detection target surface;

a light-receiving system that receives a light flux having been reflected at the detection target surface and includes a condenser optical system provided to form a secondary image of the specific pattern by condensing the light flux having been reflected at the detection target surface and a detection unit provided to detect the secondary image of the specific pattern formed via said condenser optical system; and

a means for light flux deflection provided, at least, either in an optical path of said projection system or in an optical path of said light-receiving system and having an even number of reflection surfaces to allow an incident light flux to exit at an angle that is not parallel to the incident light flux, which includes a prism having a pair of reflection surfaces that are not parallel to each other, a first transmission surface through which the incident light flux is transmitted, a first reflection surface at which the light flux having been transmitted through said first transmission surface and propagated through the inside of said prism is reflected, a second reflection surface at which the light flux having been reflected at said first reflection surface and propagated through the inside of said prism is reflected along an optical path intersecting the optical path of the light flux having been transmitted through said first transmission surface and a second transmission surface through which the light flux having been reflected at said second reflection surface and propagated through the inside of said prism is transmitted, and the angle formed by said first reflection surface and said second reflection surface set within a range of  $40^\circ$  or greater and less than  $45^\circ$  and said

FOUO - 4682800

FNKN01001/US

99/102

prism is constituted of a low-dispersion optical material with an Abbe number of 65 or higher; to detect the surface position of the detection target surface based upon an output from said detection unit; and

an alignment step in which the pattern surface of the mask or the exposure target surface of the photosensitive substrate is aligned relative to said projection optical system based upon results of a detection performed in said detection step.

86. An exposure method according to claim 85, wherein:

said prism is constituted of an optical material having a coefficient of thermal expansion equal to or lower than 1 ppm/K, which does not expand readily in heat.

87. An exposure method for implementing projection exposure of a pattern formed at a mask onto a photosensitive substrate via a projection optical system, comprising,

a detection step in which the surface position of a pattern surface of the mask or an exposure target surface of the photosensitive substrate relative to said projection optical system is detected as a surface position of a detection target surface by employing a surface position detection device that detects the surface position of the detection target surface and includes;

~~a projection system that projects a light flux from a diagonal direction onto the detection target surface;~~

a light-receiving system that receives a light flux having been reflected at the detection target surface; and

a means for light flux deflection provided, at least, either in an optical path of said projection system or in an optical path of said light-receiving system and having an even number of reflection surfaces to allow an incident light flux to exit at an angle that is not

FOUO 20010411

FNKN01001/US

100/102

parallel to the incident light flux, which includes a pair of reflection mirrors that are not parallel to each other and holding members each provided to interfit with and hold one of said pair of reflecting mirrors; to detect the surface position of the detection target surface based upon an output from said light-receiving system; and

an alignment step in which the pattern surface of the mask or the exposure target surface of the photosensitive substrate is aligned relative to said projection optical system based upon results of a detection performed in said detection step.

88. An exposure method according to claim 87, wherein:

said holding members are constituted of an optical material having a coefficient of thermal expansion equal to or lower than 1 ppm/K, which does not expand readily in heat.

89. An exposure method for implementing projection exposure of a pattern formed at a mask onto a photosensitive substrate via a projection optical system, comprising;

a detection step in which the surface position of a pattern surface of the mask or an exposure target surface of the photosensitive substrate relative to said projection optical system is detected as a surface position of a detection target surface by employing a surface position detection device that detects the surface position of the detection target surface and includes;

a projection system that projects a light flux from a diagonal direction onto the detection target surface and includes a projection optical system provided to form a primary image of a specific pattern onto the detection target surface;

a light-receiving system that receives a light flux having been reflected at the detection target surface and includes a condenser

optical system provided to form a secondary image of the specific pattern by condensing the light flux having been reflected at the detection target surface and a detection unit provided to detect the secondary image of the specific pattern formed via said condenser optical system; and

a means for light flux deflection provided, at least, either in an optical path of said projection system or in an optical path of said light-receiving system and having an even number of reflection surfaces to allow an incident light flux to exit at an angle that is not parallel to the incident light flux, which includes a pair of reflection mirrors that are not parallel to each other and holding members each provided to interfit with and hold one of said pair of reflecting mirrors; to detect the surface position of the detection target surface based upon an output from said detection unit; and

an alignment step in which the pattern surface of the mask or the exposure target surface of the photosensitive substrate is aligned relative to said projection optical system based upon results of a detection performed in said detection step.

90. An exposure method according to claim 89, wherein:

said holding members are constituted of an optical material having a coefficient of thermal expansion equal to or lower than 1 ppm/K, which does not expand readily in heat.

Add a'